

ECN000-04P-08S

Customized slip ring

CENO is a technical manufacturing company, it's has abundant experience in design and assembling for specific industries. CENO can provide you with different customized slip rings. The center hole is available from 0 to 980mm, it's used for pass through the drive shaft, gas liquid passage, also can integrate with high frequency, fiber, encoder, wave guide, gas and liquid and other joints. ECN000-04P-08S is a solid inner bore slip ring, with 4 rings of 30A power & 8 rings of signal, working speed range 0- 300rpm. It's widely used for medical equipment, rotation table, industry machine etc,. Any special request please contact with us, our professional R&D team will provide you with the best solution very soon.

Features

- ◆ Meet military standards
- ◆ High performance
- ◆ Low torque
- ◆ Stable transmission

Applications

- ◆ Measurement instruments
- ◆ Motion simulator
- ◆ Display table
- ◆ Packaging machine

Optional

- ◆ Through hole size
- ◆ Current & ring numbers
- ◆ Signal type
- ◆ IP protection grade

ECN000-04P-08S	Specification	Picture
Circuits & Current	4*30A,8*signal	
Voltage	220VAC/VDC	
Dielectric strength	≥1000V@50Hz (power) ≥300V@50Hz (signal)	
Insulation resistance	≥500MΩ@500VDC (power) ≥100MΩ@300VDC (signal)	
Electrical noise	≤70mΩ (50 rpm)	
Operating speed	0-300 rpm	
Contact material	Precious metal	
Housing material	Aluminum alloy	
IP grade	IP51	
Working temperature	-20°C ~ +60°C	

Outline Drawing

